


Nantes | Porcelain



AVAILABLE SIZES




DESCRIPTION

This inspired porcelain tile series reflects the elegance of building materials seen in the French city of Nantes. Ancient stone tile and pavers, clay and cement tile surfaces, and modern rectangular tile formats are recreated across a consistent color range. This high-quality Brazilian porcelain tile series offers a range of warm colors and subtle tone-on-tone movement in Ivory ('Argila'), Brown ('Brick'), and Black ('Antracite'), along with matching 2" x 2" mesh-mounted mosaic tile and trim. Nantes is rated PEI 4 for all Residential and Light Commercial applications.

COLORS

antracite



argila





brick



TECHNICAL INFORMATION

TILE SIZES

Nominal	Shape	Finish	Thickness	Availability
12 x 24		Matte	9.5 mm	✓
2 x 2 Mosaic		Matte	9.5 mm	✓

✓ Stock Item. ⌚ Non-Stock Item. Requires Extra Lead Time.

PERFORMANCE DATA

CHARACTERISTIC	NORMS	RESULTS
Water Absorption	ISO 10545-3	≤ 0.50 %
Abrasion Resistance (Glazed)	ISO 10545-7	4
Breaking Strength	ISO 10545-4	≤ 0.50 %
Dynamic Coefficient of Friction Wet	AcuTest	0.42
Frost Resistance	ISO 10545-12	Frost Proof
Chemical Resistance - Household Chemicals	ISO 10545-13	Class C
Chemical Resistance - Low Concentration of Acids	ISO 10545-13	Class C
Resistance to Stains	ISO 10545-14	Class A

SHADE VARIATION



V3 - MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece may vary significantly. For example "that little bit of color" on one piece of tile may be the primary color on the next piece.

WEAR CODE

4 - Rated for all residential and light commercial applications.

APPLICATIONS

	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
FLOORS	✘	✘	
WALLS / BACKSPLASH	✘	✘	✘
POOL DECKING	*	*	
EXTERNAL USE - FROST PROOF	*	*	

✘ - Has been approved for this application.
* - Information is available upon request.

NOTES

It is not recommended to stagger any tile longer than 18" more than 1/3 the length of the tile.

Minimum Grout Joint Recommendation: 3/16"

Always inspect materials prior to installation.

Always mix 2-3 cartons at a time while installing to insure the best blend.

All product images are representative only. Variation in color and shading is to be expected. Final selection should be made from actual tile samples.